

E500 G5



Intel® Mehlow platform Workstation with up to three displays support









HIGHLIGHTS

- Powerful performance with Intel® Xeon® E processor and ECC memory
- Supports up to three independent displays simultaneously via HDMI, DisplayPort, DVI-D and VGA
- Improved productivity with ASUS Control Center
- Graphics card support, including NVIDIA® Quadro® and AMD® Radeon™ Pro
- Dual M.2 for up to 32Gbps performance and data redundancy
- Convenient I/O design and ultrafast connectivity
- Dual Intel® Gigabit LAN with teaming support
- Independent software vendor (ISV) certification

Powerful performance with Intel Xeon E2100 CPUs and ECC memory

E500 G5 is built on the Intel C246 chipset and comes with a choice of the latest Intel Xeon E2100 family or 8th Generation Intel Core™ CPUs. With Intel Xeon, E500 G5 delivers powerful, optimized performance for always-on usage scenarios and supports error-correction code (ECC) memory for automatic detection and repair of single-bit memory errors, reducing the change of system crashes and data corruption to ensure reliable and responsive workstation performance.

Graphics card support

E500 G5 supports NVIDIA Quadro and AMD Radeon™ Pro graphics cards, making it the perfect workstation for content creators, media streamers and professional designers

Supports up to three independent displays simultaneously

Designers rely on multiple displays for more efficient and comfortable productivity. E500 G5 comes equipped for total display flexibility with support for up to three independent displays via HDMI, DisplayPort, DVI-D and VGA, perfect for multitasking environments..

Improved productivity with ASUS Control Center

E500 G5 features centralized IT-management with ASUS Control Center (ACC), a comprehensive control platform with a user-friendly interface that provides access to all of your workstations from anywhere via your mobile device. It is designed to improve system reliability, facilitate easy updates and provide seamless integration for small to medium-size business and enterprises for increased productivity

Dual M.2 for up to 32Gbps performance and data redundancy

E500 G5 features dual M.2 slots to unleash maximum data-transfer performance. One M.2 slot supports up to 22110-length M.2 drives via PCle 3.0 x4 for ultrafast data access. The other M.2 slot is suitable for SATA drives or Intel® Optane memory via PCle 3.0 x2 to speed up traditional hard drives.

Independent software vendor (ISV) certification

Independent software vendor (ISV) software is becoming an important factor to users in variety of industries. ASUS works in close partnership with ISV vendors, such as Adobe and Autodesk, to test and verify compatibility. This ensures ASUS workstations are reliable and highly effective for users in different fields.





SPECIFICATION

CPU 1 x Socket LGA1151

Intel® Xeon® processor E-2100 family Intel® Pentium™ processors Intel® Celeron™ processors

Intel® 9th/8th Core™ i9/i7/i5/i3 processors

Chipset Intel®C246 Chipset

Memory Total Slots: 4 (2-channel)

Capacity: Maximum up to 64GB ECC/non-ECC UDIMM

Memory Size: 16GB, 8GB, DDR4 2666/2400

Expansion Slots Total: 6

PCIEX1_1: PCI-E x1 slot, x1 Gen3 Link, from PCH PCIEX16_1: PCI-E x16 slot, x16/ x8 Gen3 Link, from CPU

PCIEX16_2: PCI-E x16 slot, x8 Gen3 Link, switched from PCIEX16_1, from CPU

PCIEX1_2: PCI-E x1 slot, x1 Gen3 Link, from PCH PCIEX16_3: PCI-E x16 slot, x4 Gen3 Link, from PCH

PCIEX16_4: PCI-E x16 slot, x4 Gen3 Link, from PCH, shared with 4 SATA

Storage SATA Controller :

Intel® C246 Chipset 8 x SATA3 6Gb/s ports

Intel® Rapid Storage Technology(RST) (For Linux/Windows)

(Support Software RAID)

Drive bay:

3 x Internal 3.5"(or 2x2.5" optional cage) drive Bay

1 x Internal 2.5" drive bay 2 x Internal 3.5"/2.5" drive bay

M.2:

1 x M.2 (SATA 6Gb/s & PCle Gen3 x2 link, NGFF 2280/2260/2242) 1 x M.2 (PCle Gen3 x4 link, NGFF 22110/2280/2260/2242)

LAN 1 x Intel® i210-AT

1 x Intel® i219-LM

Audio Realtek® ALC887 8-Channel High Definition Audio CODEC

Power Supply 300W 80PLUS Single Power Supply, Bronze

100-127/220-240V, 6/3A, 60-50Hz, Class I 500W 80PLUS Single Power Supply, Gold 100-240V, 10-6A, 50/60Hz, Class I 700W 80PLUS Single Power Supply, Gold 100-240V, 10-5A, 50/60Hz, Class I

Back Panel I/O Ports 2 x USB 3.1 Gen2 ports (1 port at Type A, 1 port at Type C)

4 x USB 3.1 Gen1 ports

1 x HDMI 1 x DisplayPort 1 x DVI-D 1 x VGA 2 x RJ-45 ports

1 x 8-channel Audio I/O ports (5 + 1 Audio jacks)

Front I/O Ports 2 x USB 3.1 Gen1

2 x USB 2.0 1 x Headphone port 1 x Microphone port

Dimension 423mm x 190mm x 435mm